

Specifications

Current Rating: 1.5A AC/DC

Voltage Rating: 30V AC/DC

Contact Resistance: 30m ohm. Max.

Insulation Resistance: 1000M ohm. min.

Withstanding Voltage: 500V AC For One Minute

Operating Temperature Range: $-55^{\circ}\text{C} \sim +105^{\circ}\text{C}$

Material And Finish

Insulator: Thermoplastic(LCP) UL94V-0

Contact: Brass or Copper Alloy

Plating: Gold Plated on Contact Area, Tin Plated on Solder Tail.

Shell: Brass or Copper Alloy, Nickel Plated


AAACONN

RoHS Compliant

TOLERANCES ARE

DRAWING BY	X, ±
CHECKED BY	.X ± 0.30
UNIT / mm	.XX ± 0.20
SCALE 1 : 1	.XXX ± 0.10
DATE	ANG ± 1°

SIZE A4 PPROJECTION



ORDER INFORMATION

USB-MINIB-H-5-x-x

SERIES

INSULATOR COLOR:

1=BLACK, 2=WHITE, 3=BLUE, 4=BEIGE

SHELL & CONTACT: 1=BRASS, 2=COPPER ALLOY

5 POSITION

HORIZONTAL 90°

AAA (HK) Electronics Co., Ltd.

www.aaaconnectors.com

Description: USB - mini B USB 2.0 Receptacle Connector 5 Position Through Hole, Right Angle