



T:1.6 Dimensions of PC board holes  
Tolerance : ±0.05(Printed-top view)

PIN	SCHEMATIC
ø1.30	

6	COVER	1	PA10T (UL94V-0)	BLACK
5	HOUSING	1	PA10T (UL94V-0)	BLACK
4	PIN	1	Brass	Ag PLATED
3	CURVE PIECE	1	Brass t=0.50	Ag PLATED
2	SPRING PIECE	1	Brass t=0.50	Ag PLATED
1	FLAT PIECE	1	Brass t=0.50	Ag PLATED
LTR	PART NAME	QTY	MATERIAL	REMARK

Specifications  
 Current Rating: 3.5A  
 Voltage Rating: 24V DC  
 Contact Resistance: 50m ohm. Max.  
 Insulation Resistance: 100M ohm. min.  
 Withstanding Voltage: 500V AC For One Minute  
 Operating Temperature Range: -25°C ~ +85°C

UNLESS OTHERWISE SPECIFIED, TOLERANCE ON DECIMAL:±0.3

**AAA**CONN

AAA (HK) Electronics Co., Ltd.

www.aaaconnectors.com

**RoHS Compliant**

TOLERANCES ARE

DRAWING BY

X.±

CHECKED BY

.X±

UNIT / mm

SCALE 1 : 1

.XX±

DATE

.XXX±

SIZE A4

PJECTION

ANG±



ORDER INFORMATION

DCPJ-007

SERIES PRODUCT NUMBER

Description: DC Power Jack 1.30mm ID, 4.00mm OD Through Hole, Right Angle