



T:1.6 Dimensions of PC board holes
Tolerance : ± 0.1 (Printed-top view)

PJ2-251-A-SMT-TR	PJ2-251-B-SMT-TR	PJ2-251-C-SMT-TR	PJ2-251-D-SMT-TR

UNLESS OTHERWISE SPECIFIED, TOLERANCE ON DECIMAL: ± 0.2

Specifications

Current Rating: 1A
Voltage Rating: 12V DC
Contact Resistance: 50m ohm. Max.
Insulation Resistance: 100M ohm. min.
Withstanding Voltage: 500V AC For One Minute
Operating Temperature Range: -25°C ~ +85°C

Material And Finish

Insulator: PA10T UL94V-0 Black
Contact: Brass or Phosphor Bronze
Plating: Gold flash over Nickel

AAACONN

RoHS Compliant

TOLERANCES ARE

DRAWING BY	X, \pm
CHECKED BY	X, \pm
UNIT / mm	.XX, \pm
SCALE 1 : 1	.XXX, \pm
DATE	ANG, \pm
SIZE A4	P PROJECTION



ORDER INFORMATION

PJ2-251-x-SMT-TR

SERIES

PACKAGING: TR = TAPE & REEL

SMT 90°

SWITCH OPTIONS: A TYPE, B TYPE, C TYPE, D TYPE

Description: 2.50mm Headphone Phone Jack Stereo/Mono Connector SMT

AAA (HK) Electronics Co., Ltd.

www.aaaconnectors.com