



Specifications

Current Rating: 5.0A
 Voltage Rating: 24V DC
 Contact Resistance: 30m ohm. Max.
 Insulation Resistance: 100M ohm. min.
 Withstanding Voltage: 500V AC For One Minute
 Operating Temperature Range: -25°C ~ +70°C

7	Insulators, Handle	Thermoplastic	UL-94V0(Black or Red)	1
6	Tip Terminal	Brass	Tin Plated	1
5	Sleeve Terminal, Cable Clamp	Brass	Tin Plated	1
4	Shim	PBT(HB)		1
3	Thread Sleeve	Brass	Nickel Plated	1
2	Coupling Ring	Brass	Nickel Plated	1
1	2.0 X 5.5 Power Plug	Brass	Nickel Plated	1
ITEM	PART NAME	MATERIAL	REMARK	QTY

AAACONN

AAA (HK) Electronics Co., Ltd.

www.aaaconnectors.com

RoHS Compliant

TOLERANCES ARE

DRAWING BY	X. ±
CHECKED BY	.X ±
UNIT / mm	.XX ±
SCALE 1 : 1	.XXX ±
DATE	ANG ±

SIZE A4

PJECTION



ORDER INFORMATION

DCPS76-x

SERIES

INSULATOR COLOR: 1=BLACK, 6=RED

Description: DC Power Plug 2.00mm ID, 5.50mm OD Solder