



SCHEMATIC				
PJ1-251-3-SMT	PJ1-251-3C-SMT	PJ1-251-4-SMT	PJ1-251-5-SMT	PJ1-251-M-SMT

UNLESS OTHERWISE SPECIFIED, TOLERANCE ON DECIMAL: ±0.2

T:1.6 Dimensions of PC board holes  
Tolerance : ±0.1(Printed-top view)

**Specifications**

- Current Rating: 1A
- Voltage Rating: 12V DC
- Contact Resistance: 50m ohm. Max.
- Insulation Resistance: 100M ohm. min.
- Withstanding Voltage: 500V AC For One Minute
- Operating Temperature Range: -25°C ~ +85°C

**Material And Finish**

- Insulator: PA6T UL94V-0 Black
- Contact: Brass or Copper Alloy
- Plating: Gold Plated

**AAA**CONN

AAA (HK) Electronics Co., Ltd.

www.aaconnectors.com

**RoHS Compliant**

TOLERANCES ARE

DRAWING BY	X. ±
CHECKED BY	.X ±
UNIT / mm	.XX ±
SCALE 1 : 1	.XXX ±
DATE	ANG ±
SIZE A4	P PROJECTION



**ORDER INFORMATION**

PJ1-251-x-SMT-TR

SERIES

PACKAGING: TR = TAPE & REEL

SMT 90°

SWITCH OPTIONS: 3=NO SWITCH, 3C=RING SWITCH, 4=TIP SWITCH, 5=TIP AND RING SWITCH  
M=MONO

Description: 2.50mm Headphone Phone Jack Stereo/Mono Connector SMT